

Biomedical FreezersMDF-436



Panasonic Biomedical Freezers offer the outstanding reliability and performance required in a wide variety of storage and research applications.



ower to cope with frequent door openings Large size 400-liter class • Digital temperature display as standard feature · Large-capacity, economical size


Chest type


Panasonic's MDF Series Biomedical Freezers offer the outstanding reliability and performance required in a wide variety of storage and research applications. In the medical field, they provide effective storage of life-saving fresh and frozen blood supplies and vaccines, as well as samples for diagnosis. In the biotechnology field, they provide effective storage of enzymes for genetic research, as well as culture media, reagents and samples for testing. In the industrial field, they are ideal for aging and temperature tests on electronic components, precision devices, and compound resins. As a storage environment, with excellent safety features, easy operability, and a host of other features, these freezers offer unsurpassed reliability and functionality. If you are looking for precision temperature controlled storage equipment, look to Panasonic.

Performance Data

Pull-down characteristics under no-load condition

MDF-237 MDF-436





Features

MDF-436

Enhanced Operation

 Front-mounted display/control panel (with microprocessor) located at convenient waist height

426 liters (15.0 cu.ft.)



Photo is

- Memory backup
- Temperature display
- Front access calibration for temperature recorder
- The control panel, alarm system and non-volatile memory are the same for all models in the series.

- · Single electrical box makes servicing simpler.
- The chamber temperature is displayed for five seconds if BUZZER key is depressed during power failure alarm.
- After a power outage, operation resumes at pre-outage settings (non-volatile memory for temperature and alarm temperature settings)
- Control panel can be reset to zero for validation.
- Two access ports (right-hand side and bottom left) (chest type)
- · Four casters and two adjustable feet

Recording Features (Optional)

Recorder can be fitted in convenient position that will not interfere with installation. Choice of optional recorders

- 7-day circular recorder (MTR-G85C-PE) and 32-day strip recorder (MTR-4015LH-PE) are available. (except MDF-U443)
- Temperature recorder with auto recharging battery
- Front access calibration for temperature recorder

Environment-Friendly

- HFC refrigerant (non-CFC, non-HCFC) refrigerant) is environment-friendly but offers superb performance.
- Pre-coated metal body causes less environmental damage than conventional paint coating.

Specifications

Model No.	MDF-436
Exterior dimensions (W x D x H)	1265 x 807 x 905 (mm) 49.8 x 31.8 x 35.6 (inch)
(AA Y D Y II)	43.0 X 31.0 X 30.0 (IIICII)
Interior dimensions	1140 x 550 x 735 (mm)
(W x D x H)	44.9 x 21.7 x 28.9 (inch)
Capacity	426L (15.0 cu. ft.)
Cooling performance	-35°C (AT: 35°C, no load)
Control range	-20°C to -35°C
Baskets	4
Access ports	17mm diameter, right-hand side and bottom left
Compressor	Hermetic, 350W
Refrigerant	HFC
Alarm system	High/low temperature alarm (SV ±5°C to ±15°C adjustable) ficatio
	Power failure Remote alarm contact
	Part replacement notification (MDF-U5312 only)
Calibration	Zero adjustment via control panel
Options	Temperature recorder (MTR-G85-PE, MTR-4015LH-PE), Panasonic DAQ system
Baskets	MDF-43B2-PW/43B3-PW

Options

Storage Baskets



or MDF-137/237 MDF-13B2-PW (set of two) MDF-13B3-PW (set of three)

MDF-43B2-PW (set of two)

MDF-43B3-PW (set of three)



Recording paper: RP-85-PW

-100°C to +50°C

Recording pen: DF-38FP-PW

MTR-85H-PW

(for MDF-U443 only)

Panasonic DAQ system

Data accuisition software MTR-5000-PW/Ethernet (LAN) Interface MTR-L03-PW or RS232C/RS485 Interface MTR-480-PW

Outer dimensions: 275(W) x 530(D) x 205(H)mm Inner dimensions: 230(W) x 480(D) x 200(H)mm

Outer dimensions: 255(W) x 420(D) x 205(H)mm Inner dimensions: 210(W) x 370(D) x 200(H)mm

or MDF-436

Temperature Recorders

MTR-G85C-PE (except MDF-U443) -100°C to +40°C

Mounting kit for chest: MDF-S740-PW

 Mounting kit for MDF-U5312 and MDF-U537D (lower room): MPR-S7-PW

 External mounting kit for MDF-U333 and MDF-U537D (upper room): MDF-S740T-PW

· Recording paper: RP-G85-PW

• Recording pen: PG-R-PW







Panasonic Healthcare Co., Ltd., Gunma Factory is certified for: Environmental management system: ISO14001

DISTRIBUTED BY:



Jl. Agung Utara Raya Blok A 36D/42 Sunter Agung Jakarta Utara 14350 Indonesia

Panasonic Healthcare Co., Ltd., Gunma Factory is

Medical devices quality management system: ISO13485

Quality management system: ISO9001

Telp. (62-21) 64716568, 70240088, 70240099, 87960123, 87960456

Fax. (62-21) 64716566, 87961123, 87961456 Email: sigmabimed@indo.net.id, sales@sigmabimed.con

certified for:

Website : www.sigmabimed.com kemenkes RI AKI



Panasonic Healthcare Co,. Ltd (Gunma Site-Biokiki Seizou Group)

1-1-1 Sakata Oizumi-Machi, Ora-Gun, Gunma 370-0596, Japan Copyright Panasonic Healthcare Co,. Ltd.

Melalui Scimed (Asia) Pte,. Ltd. Singapore