

Features

- After optimized design outdoor type condensing units look like outdoor unit of an air conditioner with the feature of easy installation and no need for rain proof protection.
- An extensive range of evaporating temp. The unit can work in a range of evaporating temp from -15°C ~10°C
- Plenty of function parts and protective devices. The refrigeration system is equipped with function parts and protective device.



Specifications OCU-NS400HFJ

Model		OCU-NS400HFJ	
Power Source For Utility Circuit		3Ø 380V 50Hz	
Power Source For Control Circuit		220V – 50Hz	
Refrigerant		R404A	
Evaporating Temp. Range		-15°C ~ 10°C	
Location Of Installation		Outdoor	
Ambient Temp.		-7°C ~ 43°C	
Nominal Capacity		9.06 kW	
Power Input		3.60 kW	
COP		2.51 kW	
Current		6.68 A	
Maximum Load Current		8.61 A	
Sound Level		54 dB(A)	
Compressor	Displacement		11.8 m ³ /h
	Oil	Type	FV32S
		Charge Volume	1.7 L
	Cooling Method		Natural Cooling
	Oil Supply Method		-
Condenser	Type		Fin Tube
	Heat Exchange Area		42 m ²
	Air Flow		5640 m ³ /h
	Motor Output X Quantity		70 x 2 W
	Condensing Pressure Control Method		High, Middle, Low three speed control
Connection Size	Gas Inlet	Ø19.05 mm (Out Diameter Brazing)	
	Liquid Outlet	Ø9.53 mm (Out Diameter Brazing)	
Dimension WxDxH		W380 x D940 x H1235 mm	
Weight (Refrigerant Not Included)		100 Kg	

DISTRIBUTED BY:



PT. SIGMA BIMED

Indonesia Sole Distributor

Jl. Agung Utara Raya Blok A 36D/42 Sunter Agung Jakarta Utara 14350 Indonesia

Telp. (62-21) 64716568, 70240088, 70240099, 87960123, 87960456

Fax. (62-21) 64716566, 87961123, 87961456

Email : sigmabimed@indo.net.id, sales@sigmabimed.com

Website : www.sigmabimed.com